



### HARK

Aufbaustrahler, AC-LED, Aluminiumdruckguss, Feinstruktur matt pulverbeschichtet, Diffusor aus Glas, 40° Ausstrahlwinkel, 350° dreh- und 90° schwenkbar, inkl. 168mm Erdspieß

Surface mounted spotlight, AC-LED, die-cast aluminium, matt powder-coated with fine textured paint, glass diffuser, 40° beam angle, 350° swiveling and 90° tilting, incl. 168mm ground spike

Faretto da soffitto, AC-LED, alluminio pressofuso, verniciato a polvere opaca, diffusore in vetro, fascio luminoso 40°, 350° girevole e 90° orientabile, picchetto da 168mm incluso

### FORIS

Strahler, Aluminiumdruckguss, matt pulverbeschichtet, AC-LED, Leuchtekopf 330° drehbar und 90° schwenkbar, inkl. Erdspieß, Entblendungsring in zwei Ausführungen als Zubehör separat ordern

Spotlight, die-cast aluminium, matt powder-coated, AC-LED, luminaire head 330° swiveling and 90° tilting, incl. ground spike, anti-glare ring in two performances to be ordered separately as accessory

Faretto in alluminio pressofuso, verniciato a polvere opaca, AC-LED, testa 330° girevole e 90° orientabile, picchetto incluso, anello antiabbagliamento come accessorio disponibile in due versioni da ordinare separatamente

**W3** = LED 3000K

LT: 25000h


**A++** - **A**

**IP 65**  

### HARK AC-LED

SYS 4,7W · 230V · CRI >80


472-0250480403011  255lm



### NEW! FORIS AC-LED

SYS 10W · 230V · CRI >80


341-0011080503011  740lm



### NEW! ENTBLENDUNGSRING / NO GLARE RING

mit Schraubverschluss / with screw lock

341-7000 Leuchte / Luminaire = 525lm



### NEW! ENTBLENDUNGSKREUZRASTER

### NEW! NO GLARE LOUVRE

mit Schraubverschluss / with screw lock

341-7001 Leuchte / Luminaire = 550lm

