



LED Strahlerlichteinsatz aus Aludruckguss
 Oberfläche in weiß, schwarz oder silber matt
 Vakuumbedampfter Alurefektor in 3 Ausstrahlwinkeln
 Leuchtenkopf 350° drehbar und 180° schwenkbar

LED spotlight, die cast aluminium
 White, black or silver matt surface
 Vacuum deposited aluminium reflector, 3 beam angles
 Spotlight head 350° swiveling and 180° tilting

Proiettore a LED a tensione di rete
 Finitura in bianco, nero o grigio opaco
 Ottiche in alluminio in 3 fasci di emissione
 Proiettore girevole a 350°, orientabile a 180°

Projecteur en LED à tension de red
 Fini en blanc, noir ou gris mat
 Réflecteur en aluminium en 3 angles d'émission
 Projecteur tournant à 350°, pivotant à 180°

W2 = LED 2700K
 W3 = LED 3000K
 W4 = LED 3500K



IP20

RIDE LENS TURN LICHTEINSATZ / RIDE LENS TURN LIGHT INSERT

220-240V AC · CRI >90 · Binning SDCM 3

SYS 19W

634-006010123XXY		1400lm
634-006010129XXY		1530lm
634-006010124XXY		1400lm
634-006010623XXY	+	1330lm
634-006010629XXY	+	1450lm
634-006010624XXY	+	1330lm
634-006010323XXY		1400lm
634-006010329XXY		1530lm
634-006010324XXY		1400lm

ARTIKELNUMMER ERGÄNZEN / COMPLETE CODE

XX = FARBE/COLOUR

Y = DIMMBAR/DIMMABLE

white = 05
 black = 06
 aluminium anodized = 08

switchable = 0
 DALI dimm = d

