



Schwenkbarer LED Einbauspot aus Aluminium  
 Oberfläche in schwarz, perlchrom oder chrom  
 Optisch geschliffene Glaslinse  
 Lichtkegel stufenlos fokussierbar 10° - 60°  
 Energieeffiziente LEDs mit hoher Farbwiedergabe

LED recessed orientable aluminium spotlight  
 Black, silver matt or chrome finish  
 Sanded glass lens  
 Rotating head with zoom function 10° - 60°  
 High colour rendering energy efficient LED

Incasso orientabile a LED in alluminio  
 Finitura in nero, cromo opaco o cromo  
 Lente in vetro levigato  
 Testa girevole con funzione zoom da 10° - 60°  
 LED di efficienza energetica ad alta resa cromatica

Encastré orientable à LED en aluminium  
 Fini en noir, chrome mat ou chrome  
 Lentille en verre molé  
 Tête tournante avec fuction de zoom de 10° - 60°  
 Efficientes LED à haute reproduction des couleurs

**W3** = LED 3000K  
**W4** = LED 4000K

LED 2700K auf Anfrage / on request



IP20


## ZHOOM R

CRI>90  
 exkl. LED Konverter (separat ordern) / excl. LED converter (order separately)

SYS 2W · 500mA

**56-85034ng1** **W3** 153lm  
**56-85037ng1** **W3** 153lm  
**56-85039ng1** **W3** 153lm

**56-85035ng1** **W4** 163lm  
**56-85036ng1** **W4** 163lm  
**56-85038ng1** **W4** 163lm



## LED CONVERTER ZHOOM

24-122635	<b>6W</b>	schaltbar/switchable	for 500mA	L 58 x B 31 x H 22mm
24-122428	<b>6W</b>	1 - 10V / PUSH Dimm.	for 500mA	L 67 x B 50 x H 22mm
24-122201	<b>20W*</b>	schaltbar/switchable	for 500mA	L 111 x B 52 x H 22mm
24-123400	<b>20W*</b>	1 - 10V / PUSH Dimm.	for 500mA	L 111 x B 52 x H 22mm
24-151403	<b>20W*</b>	DALI Dimm.	for 500mA	L 111 x B 52 x H 22mm

\* nicht für den Einbau in Unterputzdose Ø68 geeignet  
 \* not suitable for mounting in housing Ø68

