

TECHNICAL DATA SHEET


200CENT ROUND 250LM FIX MAXITRIM IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Fix (not adjustable) 0° - 0°

Ø27 mm - h = 95 mm

Material: Aluminium



Ref N° 200 BLACK

Black
Nero
Schwarz
Zwart
Noir
Negro



Ref N° 200 WHITE

White
Bianco
Weiß
Wit
Blanc
Blanco

200CENT ROUND FIX IP54 250LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 516 27 531	REF N° 516 27 931	REF N° 516 27 831	REF N° 516 27 731

3 W - 250LM - 2 step MacAdam - **A+**
Serial wiring - - - -
Requires remote LED driver - 1050mA
Standard narrowbeam 12° - Optional 8° beam
Ultra low glare (UGR < 13)




REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 39W

REF N° 697 00 025 min.2W max. 50W

230V/50Hz - - current controlled
 - - IP20 - 1050mA - not dimmable



INSTALLATION KIT

REF N° 682 01 000 optimal leaf springs for concrete ceiling installation

REF N° 680 01 027 standard holesaw Ø 27 mm

REMOTE LED DRIVER DIM

REF N° 697 60 025 min.3W max. 60W

1-10V DALI PUSH

REF N° 697 70 050 min 2W max 45W PHASE DIM

230V/50Hz - - current controlled
 - - IP20 - 1050mA - dimmable



BEAM ANGLES

STANDARD (included) beam angle 12°
REF N° 203 20 008 (option) beam angle 8°

Ask for a bespoke solution or your favorite RAL color
Chiedere una soluzione personalizzata con il vostro colore RAL preferito
Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe
Vraag om een niet standaard afwerking of je favoriete RAL kleur
Demandez une solution sur mesure ou votre couleur RAL préférée
Solicite una solución a medida o su color favorito de la carta RAL

WWW.BRICKINTHEWALL.EU

BRICK IN THE WALL®
invisible integration of light

TECHNICAL DATA SHEET


200CENT ROUND 500LM FIX MAXITRIM IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Fix (not adjustable) 0° - 0°

Ø27 mm - h = 95 mm

Material: Aluminium



Ref N° 200 BLACK

Black
Nero
Schwarz
Zwart
Noir
Negro




Ref N° 200 WHITE

White
Bianco
Weiß
Wit
Blanc
Blanco

200CENT ROUND FIX IP54 500LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 516 28 531	REF N° 516 28 931	REF N° 516 28 831	REF N° 516 28 731

5,9 W - 500LM - 2 step MacAdam - **A+**
Serial wiring - - **CE** - -
Requires remote LED driver - 700mA
Standard Perfectbeam 24°-
Ultra low glare (UGR < 13)




REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 32W

REF N° 697 00 025 min.2W max. 50W

230V/50Hz - - current controlled
 - **CE** - IP20 - 700mA - not dimmable



INSTALLATION KIT

REF N° 682 01 000 optimal leaf springs for concrete ceiling installation

REF N° 680 01 027 standard holesaw Ø 27 mm



BEAM ANGLES

STANDARD (included) beam angle 24°

REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max. 60W

1-10V DALI PUSH

REF N° 697 30 015 min 2W max 20W DALI

REF N° 697 60 015 min 2W max 20W 1-10V PUSH

REF N° 697 77 010 min 2W max 10W PHASE DIM

REF N° 697 77 020 min 11W max 20W PHASE DIM

230V/50Hz - - current controlled
 - **CE** - IP20 - 700mA - dimmable

Ask for a bespoke solution or your favorite RAL color

Chiedere una soluzione personalizzata con il vostro colore RAL preferito

Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe

Vraag om een niet standaard afwerking of je favoriete RAL kleur

Demandez une solution sur mesure ou votre couleur RAL préférée

Solicite una solución a medida o su color favorito de la carta RAL

WWW.BRICKINTHEWALL.EU

BRICK IN THE WALL®
invisible integration of light

TECHNICAL DATA SHEET


200CENT ROUND 750LM FIX MAXITRIM IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Fix (not adjustable) 0° - 0°

Ø27 mm - h = 95 mm

Material: Aluminium



Ref N° 200 BLACK

Black
Nero
Schwarz
Zwart
Noir
Negro




Ref N° 200 WHITE

White
Bianco
Weiß
Wit
Blanc
Blanco

200CENT ROUND FIX IP54 750LM CRI 92

2400°K	2700°K	3000°K	4000°K
REF N° 516 29 531	REF N° 516 29 931	REF N° 516 29 831	REF N° 516 29 731

6,2 W - 750LM - 2 step MacAdam - **A+**
Serial wiring - - - -
Requires remote LED driver - 250mA
Standard beam angle 36°




REMOTE LED DRIVER ON/OFF

REF N° 697 00 040 min.2W max. 30W

REF N° 697 00 080 min.27W max. 67W

230V/50Hz - - current controlled
 - - IP20 - 250mA - not dimmable



INSTALLATION KIT

REF N° 682 01 000 optimal leaf springs for concrete ceiling installation

REF N° 680 01 027 standard holesaw Ø 27 mm

REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max. 30W

1-10V DALI PUSH

REF N° 697 30 070 min 33W max 65W DALI

REF N° 697 60 080 min 27W max 67W 1-10V PUSH

REF N° 697 72 020 min 6W max 12,5W PHASE DIM

230V/50Hz - - current controlled
 - - IP20 - 250mA - dimmable



BEAM ANGLES

STANDARD (included) beam angle 36°

Ask for a bespoke solution or your favorite RAL color
Chiedere una soluzione personalizzata con il vostro colore RAL preferito
Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe
Vraag om een niet standaard afwerking of je favoriete RAL kleur
Demandez une solution sur mesure ou votre couleur RAL préférée
Solicite una solución a medida o su color favorito de la carta RAL

WWW.BRICKINTHEWALL.EU


BRICK IN THE WALL®
invisible integration of light

TECHNICAL DATA SHEET

200CENT ROUND 1000LM FIX MAXITRIM IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Fix (not adjustable) 0° - 0°

 Ø27 mm - h = 95 mm

Material: Aluminium



Ref N° 200 BLACK

Black
Nero
Schwarz
Zwart
Noir
Negro





Ref N° 200 WHITE

White
Bianco
Weiß
Wit
Blanc
Blanco

200CENT ROUND FIX IP54 1000LM CRI 92

2700°K	3000°K
REF N° 516 26 931	REF N° 516 26 831


7,1 W - 1000LM - 2 step MacAdam - **A+**
Serial wiring -  -  -  - 
Requires remote LED driver - 600mA
Perfect beam 28°



REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 32W

230V/50Hz -  - current controlled
 -  - IP20 - 600mA - not dimmable



INSTALLATION KIT

REF N° 682 01 000 optimal leaf springs for concrete ceiling installation

REF N° 680 01 027 standard holesaw Ø 27 mm

REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max. 60W

1-10V DALI PUSH

REF N° 697 30 015 min 2W max 20W DALI

REF N° 697 60 015 min 2W max 20W 1-10V PUSH

REF N° 697 76 020 min 2W max 20W PHASE DIM

230V/50Hz -  - current controlled
 -  - IP20 - 600mA - dimmable



BEAM ANGLES

STANDARD (included) beam angle 28°

Ask for a bespoke solution or your favorite RAL color
Chiedere una soluzione personalizzata con il vostro colore RAL preferito
Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe
Vraag om een niet standaard afwerking of je favoriete RAL kleur
Demandez une solution sur mesure ou votre couleur RAL préférée
Solicite una solución a medida o su color favorito de la carta RAL

WWW.BRICKINTHEWALL.EU

BRICK IN THE WALL®
invisible integration of light