

TECHNICAL DATA SHEET

200CENT SQUARE 250LM SWING 70 TRIMLESS IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Adjustable 0° - 68°

114x134 mm - h = 50 mm

Material : CALCYT® plaster



200CENT SQUARE SWING 70 250LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N°	REF N°	REF N°	REF N°
560 27 530	560 27 930	560 27 830	560 27 730

3W - 250lm - 2 Step MacAdam -
Serial wiring - - - -
Requires remote LED driver - 1050mA
Narrow beam 12° - Ultra low glare (UGR < 13)

REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 39W

REF N° 697 00 025 min.2W max. 50W




230V/50Hz - - current controlled
 - - IP20 - 1050mA - not dimmable

REMOTE LED DRIVER DIM

REF N° 697 60 025 min. 2W max. 60W


1-10V DALI PUSH

230V/50Hz - - current controlled
 - - IP20 - 1050mA - dimmable



INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm
REF N° 200 99 025 installation system for gypsum ceiling 25 mm
REF N° 200 99 030 installation system for gypsum ceiling 30 mm
REF N° 827 00 000 Concrete box 200CENT - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 12°



TECHNICAL DATA SHEET

200CENT SQUARE 500LM SWING 70 TRIMLESS IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Adjustable 0° - 68°

114x134 mm - h = 50 mm

Material : CALCYT® plaster



200CENT SQUARE SWING 70 500LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 560 28 530	REF N° 560 28 930	REF N° 560 28 830	REF N° 560 28 730

5,9 W - 500lm - 2 Step MacAdam - **A+**
Serial wiring - - - -
Requires remote LED driver - 700mA
Perfect beam 24° - Ultra low glare (UGR < 13)

REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 32W

REF N° 697 00 025 min.2W max. 50W

230V/50Hz - - current controlled
 - - IP20 - 700mA - not dimmable

REMOTE LED DRIVER DIM

REF N° 697 60 040 min. 3W max. 60W
1-10V DALI PUSH




REF N° 697 77 010 min. 2W max. 10W PHASE DIM

REF N° 697 77 020 min. 11W max. 20W PHASE DIM

REF N° 697 30 015 min. 2W max. 20W DALI


REF N° 697 60 015 min. 2W max. 20W 1-10V PUSH

230V/50Hz - - current controlled
 - - IP20 - 700mA - dimmable



INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm
REF N° 200 99 025 installation system for gypsum ceiling 25 mm
REF N° 200 99 030 installation system for gypsum ceiling 30 mm
REF N° 827 00 000 Concrete box 200CENT - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 24°



TECHNICAL DATA SHEET

200CENT SQUARE 750LM SWING 70 TRIMLESS IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Adjustable 0° - 68°

114x134 mm - h = 50 mm

Material : CALCYT® plaster



REF N° 200 BL BL
Black - Black



REF N° 200 WH BL
White - Black



REF N° 200 BL WH
Black - White



REF N° 200 WH WH
White - White

200CENT SQUARE SWING 70 750LM CRI 92

2400°K	2700°K	3000°K	4000°K
REF N° 560 29 530	REF N° 560 29 930	REF N° 560 29 830	REF N° 560 29 730

6,2 W - 750lm - 2 Step MacAdam - **A+**
Serial wiring -  -  -  - 
Requires remote LED driver - 250 mA
Standard beam angle 36°

REMOTE LED DRIVER ON/OFF

REF N° 697 00 040 min.1W max. 30W

REF N° 697 00 080 min. 27W max. 67W

230V/50Hz -  - current controlled
 -  - IP20 - 250mA - not dimmable




REMOTE LED DRIVER DIM

REF N° 697 60 040 min. 3W max. 30W
1-10V DALI PUSH

REF N° 697 60 150 min. 20W max. 100W 1-10V


REF N° 697 30 150 min. 20W max. 100W DALI

230V/50Hz -  - current controlled
 -  - IP20 - 250mA - dimmable



INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm
REF N° 200 99 025 installation system for gypsum ceiling 25 mm
REF N° 200 99 030 installation system for gypsum ceiling 30 mm
REF N° 827 00 000 Concrete box 200CENT - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 36°

