

TECHNICAL DATA SHEET

200CENT ROUND 250LM FIX TRIMLESS IP20

INDOOR - INTERNO - INNERBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Fix (not adjustable) 0° - 0°

114x134 mm - h = 90 mm

Material: CALCYT® plaster



Ref N° 200 BLACK

Black
Nero
Schwarz
Zwart
Noir
Negro



Ref N° 200 WHITE

White
Bianco
Weiß
Wit
Blanc
Blanco



Ref N° 200 CHROME

Chrome
Cromo
Chrom
Chroom
Chrome
Cromo



Ref N° 200 GOLD

Gold
Oro
Gold
Goud
Or
Oro



Ref N° 200 COPPER

Copper
Rame
Kupfer
Koper
Cuivre
Cobre

200CENT ROUND FIX IP20 250LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 250 27 530	REF N° 250 27 930	REF N° 250 27 830	REF N° 250 27 730

3 W - 250LM - 2 step MacAdam - **A+**
Serial wiring - - **CE** - -
Requires remote LED driver - 1050mA
Standard narrowbeam 12° - Optional 8° beam
Ultra low glare (UGR < 13)

REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 39W

REF N° 697 00 025 min.2W max. 50W

230V/50Hz - - current controlled
CE - IP20 - 1050mA - not dimmable




REMOTE LED DRIVER DIM

REF N° 697 60 025 min.3W max. 60W

1-10V DALI PUSH

REF N° 697 70 050 min 2W max 45W PHASE DIM

230V/50Hz - - current controlled
CE - IP20 - 1050mA - dimmable




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 200 99 025 installation system for gypsum ceiling 25 mm

REF N° 200 99 030 installation system for gypsum ceiling 30 mm

REF N° 827 00 000 Concrete box 200Cent - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 12°

REF N° 203 20 008 (option) beam angle 8°

Ask for a bespoke solution or your favorite RAL color

Chiedete una soluzione personalizzata con il vostro colore RAL preferito

Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe

Vraag om een niet standaard afwerking of je favoriete RAL kleur

Demandez une solution sur mesure ou votre couleur RAL préférée

Solicite una solución a medida o su color favorito de la carta RAL

WWW.BRICKINTHEWALL.EU

BRICK IN THE WALL®
invisible integration of light

TECHNICAL DATA SHEET

200CENT ROUND 500LM FIX TRIMLESS IP20

INDOOR - INTERNO - INNERBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Fix (not adjustable) 0° - 0°

114x134 mm - h = 90 mm

Material: CALCYT® plaster



Ref N° 200 BLACK

Black
Nero
Schwarz
Zwart
Noir
Negro



Ref N° 200 WHITE

White
Bianco
Weiß
Wit
Blanc
Blanco



Ref N° 200 CHROME

Chrome
Cromo
Chrom
Chroom
Chrome
Cromo



Ref N° 200 GOLD

Gold
Oro
Gold
Goud
Or
Oro



Ref N° 200 COPPER

Copper
Rame
Kupfer
Koper
Cuivre
Cobre

200CENT ROUND FIX IP20 500LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 250 28 530	REF N° 250 28 930	REF N° 250 28 830	REF N° 250 28 730

5,9 W - 500LM - 2 step MacAdam - **A+**
Serial wiring - - - -
Requires remote LED driver - 700mA
Standard Perfectbeam 24° - Optional 44° beam
Ultra low glare (UGR < 13)

REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 32W

REF N° 697 00 025 min.2W max. 50W

230V/50Hz - - current controlled
 - - IP20 - 700mA - not dimmable

REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max. 60W

1-10V DALI PUSH




REF N° 697 30 015 min 2W max 20W DALI

REF N° 697 60 015 min 2W max 20W 1-10V PUSH

REF N° 697 77 010 min 2W max 10W PHASE DIM

REF N° 697 77 020 min 11W max 20W PHASE DIM

230V/50Hz - - current controlled
 - - IP20 - 700mA - dimmable




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 200 99 025 installation system for gypsum ceiling 25 mm

REF N° 200 99 030 installation system for gypsum ceiling 30 mm

REF N° 827 00 000 Concrete box 200Cent - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 24°

REF N° 203 20 044 (option) beam angle 44°

Ask for a bespoke solution or your favorite RAL color
Chiedere una soluzione personalizzata con il vostro colore RAL preferito
Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe
Vraag om een niet standaard afwerking of je favoriete RAL kleur
Demandez une solution sur mesure ou votre couleur RAL préférée
Solicite una solución a medida o su color favorito de la carta RAL

WWW.BRICKINTHEWALL.EU

BRICK IN THE WALL®
invisible integration of light

TECHNICAL DATA SHEET

200CENT ROUND 750LM FIX TRIMLESS IP20

INDOOR - INTERNO - INNERBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Fix (not adjustable) 0° - 0°

114x134 mm - h = 90 mm

Material: CALCYT® plaster



Ref N° 200 BLACK

Black
Nero
Schwarz
Zwart
Noir
Negro



Ref N° 200 WHITE

White
Bianco
Weiß
Wit
Blanc
Blanco



Ref N° 200 CHROME

Chrome
Cromo
Chrom
Chroom
Chrome
Cromo



Ref N° 200 GOLD

Gold
Oro
Gold
Goud
Or
Oro



Ref N° 200 COPPER

Copper
Rame
Kupfer
Koper
Cuivre
Cobre

200CENT ROUND FIX IP20 750LM CRI 92

2400°K	2700°K	3000°K	4000°K
REF N° 250 29 530	REF N° 250 29 930	REF N° 250 29 830	REF N° 250 29 730

6,2 W - 750LM - 2 step MacAdam - **A+**
Serial wiring - - **CE** - -
Requires remote LED driver - 250mA
Standard beam angle 36°

REMOTE LED DRIVER ON/OFF

REF N° 697 00 040 min.2W max. 30W

REF N° 697 00 080 min.27W max. 67W

230V/50Hz - - current controlled
 - **CE** - IP20 - 250mA - not dimmable

REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max. 30W




1-10V DALI PUSH

REF N° 697 30 070 min 33W max 65W DALI

REF N° 697 60 080 min 27W max 67W 1-10V PUSH

REF N° 697 72 020 min 6W max 12,5W PHASE DIM

230V/50Hz - - current controlled
 - **CE** - IP20 - 250mA - dimmable




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 200 99 025 installation system for gypsum ceiling 25 mm

REF N° 200 99 030 installation system for gypsum ceiling 30 mm

REF N° 827 00 000 Concrete box 200Cent - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 36°

Ask for a bespoke solution or your favorite RAL color
Chiedere una soluzione personalizzata con il vostro colore RAL preferito
Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe
Vraag om een niet standaard afwerking of je favoriete RAL kleur
Demandez une solution sur mesure ou votre couleur RAL préférée
Solicite una solución a medida o su color favorito de la carta RAL

WWW.BRICKINTHEWALL.EU

BRICK IN THE WALL®
invisible integration of light

TECHNICAL DATA SHEET

200CENT ROUND 1000LM FIX TRIMLESS IP20

INDOOR - INTERNO - INNERBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Fix (not adjustable) 0° - 0°

114x134 mm - h = 90 mm

Material: CALCYT® plaster



Ref N° 200 BLACK

Black
Nero
Schwarz
Zwart
Noir
Negro




Ref N° 200 WHITE

White
Bianco
Weiß
Wit
Blanc
Blanco



Ref N° 200 CHROME

Chrome
Cromo
Chrom
Chroom
Chrome
Cromo



Ref N° 200 GOLD

Gold
Oro
Gold
Goud
Or
Oro



Ref N° 200 COPPER

Copper
Rame
Kupfer
Koper
Cuivre
Cobre

200CENT ROUND FIX IP20 1000LM CRI 92

2700°K	3000°K
REF N° 250 26 930	REF N° 250 26 830

7,1 W - 1000LM - 2 step MacAdam - **A+**
Serial wiring - - **CE** - -
Requires remote LED driver - 600mA
Perfect beam 28°

REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 32W

230V/50Hz - - current controlled
 - **CE** - IP20 - 600mA - not dimmable

REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max. 60W




1-10V DALI PUSH

REF N° 697 30 015 min 2W max 20W DALI

REF N° 697 60 015 min 2W max 20W 1-10V PUSH

REF N° 697 76 020 min 2W max 20W PHASE DIM

230V/50Hz - - current controlled
 - **CE** - IP20 - 600mA - dimmable




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 200 99 025 installation system for gypsum ceiling 25 mm

REF N° 200 99 030 installation system for gypsum ceiling 30 mm

REF N° 827 00 000 Concrete box 200Cent - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 28°

Ask for a bespoke solution or your favorite RAL color
Chiedete una soluzione personalizzata con il vostro colore RAL preferito
Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe
Vraag om een niet standaard afwerking of je favoriete RAL kleur
Demandez une solution sur mesure ou votre couleur RAL préférée
Solicite una solución a medida o su color favorito de la carta RAL

WWW.BRICKINTHEWALL.EU

BRICK IN THE WALL®
invisible integration of light